



NOTES:

CONCRETE SIDEWALK – 5" CONCRETE WITH 4" CLASS 5

BITUMINOUS TRAIL – 2 ½" BITUMINOUS WEAR (TYPE SP 9.5 WEARING COURSE MIX SPWEA230B) WITH 6" CLASS 5

SIDEWALKS OR TRAIL CROSSING COMMERCIAL OR INDUSTRIAL DRIVEWAYS SHALL BE CONSTRUCTED TO DRIVEWAY REQUIREMENTS INDICATED ON STR-9

RESIDENTIAL STREETS SHALL BE 7 TON DESIGN UNLESS OTHERWISE SPECIFIED

SUBGRADE MUST BE APPROVED BY THE ENGINEER

① SUBCUT WHERE UNSUITABLE MATERIALS EXIST AS DIRECTED BY THE ENGINEER IN THE FIELD. SUBCUT AREAS SHALL BE BACKFILLED WITH SUITABLE MATERIAL AS DETERMINED BY THE ENGINEER



LAST REVISION
JANUARY 2018

RESIDENTIAL STREET TYPICAL SECTION

CITY OF MAPLE GROVE ENGINEERING
& PUBLIC WORKS DEPARTMENTS

STANDARD
PLATE #
STR-6